

ONE FLOR EUROPE



Declaration Owner

Oneflor Europe bv

Wittestraat 10 - B-8501 HEULE

Belgium

www.oneflor-europe.com | info@oneflor-europe.com

+32 (0)56 41 06 04

Product

MERCURY RIGID SPC Click

(UNSPSC Class Code 30161707/CSI Code 09 65 00)

Functional Unit

The functional unit is one square meter of flooring installed and maintained over a 1-year period.

EPD Number and Period of Validity

SCS-EPD-10434

EPD Valid May 19, 2025 through May 18, 2030

Product Category Rule

The International EPD System, 2024-04-30, PCR 2019:14

CONSTRUCTION PRODUCTS, version 1.3.4, VALID UNTIL: 2025-06-20.

The International EPD System, C-PCR-004 (TO PCR 2019:14), RESILIENT, TEXTILE AND LAMINATE FLOOR COVERINGS (EN 16810:2017), VERSION: 2024-04-30, VALID UNTIL: 2025-06-20

CEN standard EN 15804 serves as the core Product Category Rules (PCR)

Program Operator

SCS Global Services

2000 Powell Street, Ste. 600, Emeryville, CA 94608

+1.510.452.8000 | www.SCSglobalServices.com



Declaration Owner:	Oneflor Europe bv														
Address:	Wittestraat 10 - B-8501 HEULE Belgium														
Declaration Number:	SCS-EPD-10434														
Declaration Validity Period:	EPD Valid May 19, 2025 through May 18, 2030														
Program Operator:	SCS Global Services														
Declaration URL Link:	https://www.scsglobalservices.com/certified-green-products-guide														
LCA Practitioner:	Gerard Mansell, Ph.D., SCS Global Services														
LCA Software and LCI database:	OpenLCA v2.1 software and the Ecoinvent v3.10 database														
Product RSL:	1 year														
Markets of Applicability:	Europe														
EPD Type:	Product-Specific														
EPD Scope:	Cradle-to-Grave and Module D														
Independent critical review of the LCA and data, according to ISO 14044 and ISO 14071	☐ internal ☒ external														
LCA Reviewer:	 Lindita Bushi, PhD, Athena Sustainable Materials Institute														
Product Category Rule:	The International EPD System, 2024-04-30, PCR 2019:14 CONSTRUCTION PRODUCTS, version 1.3.4, VALID UNTIL: 2025-06-20.														
PCR Review conducted by:	The Technical Committee of the International EPD® System. Review chair: Claudia A. Peña, University of Concepción, Chile.														
Complementary Product Category Rule:	The International EPD System, C-PCR-004 (TO PCR 2019:14), RESILIENT, TEXTILE AND LAMINATE FLOOR COVERINGS (EN 16810:2017), VERSION: 2024-04-30, VALID UNTIL: 2025-06-20														
Complementary PCR Review conducted by:	The Technical Committee of the International EPD® System.														
Independent verification of the declaration and data, according to ISO 14025 and the PCR	☐ internal ☒ external														
EPD Verifier:	 Lindita Bushi, PhD, Athena Sustainable Materials Institute														
Declaration Contents:	<table border="0"> <tr> <td>1. Oneflor Europe bv</td> <td>2</td> </tr> <tr> <td>2. Product.....</td> <td>2</td> </tr> <tr> <td>3. LCA: Calculation Rules</td> <td>6</td> </tr> <tr> <td>4. LCA: Scenarios and Additional Technical Information</td> <td>11</td> </tr> <tr> <td>5. LCA: Results.....</td> <td>14</td> </tr> <tr> <td>6. LCA: Interpretation</td> <td>19</td> </tr> <tr> <td>7. References.....</td> <td>19</td> </tr> </table>	1. Oneflor Europe bv	2	2. Product.....	2	3. LCA: Calculation Rules	6	4. LCA: Scenarios and Additional Technical Information	11	5. LCA: Results.....	14	6. LCA: Interpretation	19	7. References.....	19
1. Oneflor Europe bv	2														
2. Product.....	2														
3. LCA: Calculation Rules	6														
4. LCA: Scenarios and Additional Technical Information	11														
5. LCA: Results.....	14														
6. LCA: Interpretation	19														
7. References.....	19														
Disclaimers: This EPD conforms to ISO 14025, 14040, 14044, and EN 15804:2012+A2:2019/AC:2021. Scope of Results Reported: The PCR requirements limit the scope of the LCA metrics such that the results exclude environmental and social performance benchmarks and thresholds, and exclude impacts from the depletion of natural resources, land use ecological impacts, ocean impacts related to greenhouse gas emissions, risks from hazardous wastes and impacts linked to hazardous chemical emissions. Accuracy of Results: Due to PCR constraints, this EPD provides estimations of potential impacts that are inherently limited in terms of accuracy. Comparability: EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025. The owner of the declaration shall be liable for the underlying information and evidence; SCS shall not be liable with respect to manufacturer information, life cycle assessment data, and evidence supplied or made available to SCS.															

1. Oneflor Europe bv

Oneflor-Europe is a leading global supplier of LVT flooring, based in Kortrijk, Belgium. They provide innovative flooring solutions to customers throughout Europe and beyond, serving both residential and commercial sectors.


Since its founding in 2016, Oneflor-Europe has been driven by a commitment to innovation, quality, design, and exceptional service.

Oneflor-Europe works closely with distributors, retailers, hotels, and architects to build strong partnerships.

2. Product


2.1 PRODUCT DESCRIPTION

Product Name	Representative Thickness	Use Class Code	Description
MERCURY RIGID SPC Click	5.0 mm	UNSPSC Class Code 30161700	SPC (stone plastic composite vinyl flooring) Vinyl Flooring is made primarily from polyvinyl chloride (PVC), calcium carbonate (limestone), and additives Rigid Click LVT flooring, class 33, 10 years guarantee commercial use / 25 years guarantee residential use



2.2 PRODUCT FLOW DIAGRAM

A flow diagram illustrating the production processes and life cycle phases included in the scope of the EPD is provided below.



2.3 APPLICATION

The product provides the primary function of flooring for interior applications. The flooring product is used in various residential and commercial applications including retail, healthcare, education, and hospitality.

2.4 DECLARATION OF METHODOLOGICAL FRAMEWORK

The scope of the EPD is cradle-to-grave and Module D, including raw material extraction and processing, transportation, product manufacture, product delivery, installation and use, and product disposal. The LCA is conducted using an attributional approach. The environmental loads and benefits resulting from recyclable materials leaving a product system (Module D) are negligible. Cut-off and allocation procedures are described below and conform to the PCR and ISO standards.

The life cycle phases included in the product system boundary are shown below.

Table 1. Life cycle phases included in the Oneflor flooring product system boundary.

	Product			Construction Process		Use							End-of-life				Benefits and loads beyond the system boundary
	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
	Raw material extraction and processing	Transport to manufacturer	Manufacturing	Transport	Construction - installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, recovery and/or recycling potential
Modules Declared	x	x	x	x	x	n/a	x	n/a	n/a	n/a	n/a	n/a	x	x	x	x	x
Geography	GLO	GLO	CN	RER	RER	e/u	RER	e/u	e/u	e/u	e/u	e/u	RER	RER	RER	RER	GLO
Share of specific data	>90%			>90%		-	-	-	-	-	-	-	-	-	-	-	-
Variation - products	-			-		-	-	-	-	-	-	-	-	-	-	-	-
Variation - sites	-			-		-	-	-	-	-	-	-	-	-	-	-	-

X = Included in system boundary

GLO = Global; CN = China; RER – Regional Europe

n/a = Module not applicable

2.5 TECHNICAL DATA

Technical specifications for the flooring product are summarized in Table 2.

Table 2. Product characteristics for the **MERCURY RIGID SPC Click** flooring product.

Characteristic			Description			
Sustainable certifications			-			
VOC emissions test method			EN 16516			
Use Classification (according to EN ISO 10874)			Commercial: 33			
Characteristic			Average Value	Unit	Min Value	Max Value
Product thickness			5.00 (0.197)	mm (in)	4.90 (0.192)	5.13 (0.0202)
Wear layer thickness (where applicable)			0.55 (0.022)	mm (in)	0.50 (0.0197)	0.62 (0.0244)
Product weight			8,200 (26.87)	g/m² (oz/ft²)	8,060 (26.41)	8,600 (28.18)
Product Form	Tiles/Planks	Width	242.5 (9.55)	mm (in)	180 (7.09)	305 (12.01)
		Length	915 (36.02)	mm (in)	610 (24.02)	1220 (48.03)

2.6 MARKET PLACEMENT/APPLICATION RULES

Technical specifications of the flooring product are summarized above. Detailed product performance results can be found on the manufacturer's website www.oneflor-europe.com.

2.7 PROPERTIES OF DECLARED PRODUCT AS DELIVERED

The flooring product is delivered for installation in the form of tiles of various dimensions.

2.8 MATERIAL COMPOSITION

The vinyl flooring product (UNSPSC Class Code 30161700/CSI Code 09 65 00) is manufactured at the production facility in China. The primary materials include PVC, plasticizers, fillers and stabilizers.

Table 3. Material content for the flooring products in kg per square meter and percent of total mass

Material	MERCURY RIGID SPC Click	
	kg/m ²	%
PVC	1.93	22%
Filler	3.82	44%
Regrind	2.57	29%
Plasticizer	0.00	0%
Plastics	0.162	1.8%
Pigment	0.00	0%
Other	0.177	2%
Total Product	8.77	100%

In conformance with the PCR, product materials were reviewed for the presence of any toxic or hazardous chemicals. Based on a review of the product components provided by the manufacturer, no chemicals regulated by the European Union Registration, Evaluation, Authorisation and restriction of chemicals (REACH) on Substances of Very High Concern were identified in the product or product components. Additionally, there are no releases of such substances associated with the production, use or maintenance of the product.

2.9 MANUFACTURING

The product is manufactured at a production facility in China. The manufacturer provided primary data for their annual production, resource use and electricity consumption and waste generation at the facility. Electricity consumption is modeled using Ecoinvent datasets for the regional electricity grid resource mix.

The production of the flooring involves the following general manufacturing processes. The raw materials are first mixed and heated. The mixture is then calendared into a sheet to create the backing or the transparent wear layers. The sheets are cut and laminated with a print film. Finally, the product is cut into tiles and packaged. Quality checks are made at each step of the production process.

2.10 PACKAGING

The product is packaged for shipment using plastic wrap, corrugated board and wooden pallets.

Table 4. Material content for the flooring product packaging in kg per square meter of flooring.

Material	MERCURY RIGID SPC Click		
	kg/m ²	%	Biogenic Material
Corrugate/Paper	0.271	3.1%	Yes
Plastic	3.80x10 ⁻³	0.043%	No
Wood	0.248	2.8%	Yes
Total Packaging	0.523	6%	

2.11 PRODUCT INSTALLATION

Installation of the product is accomplished using hand tools with negligible impacts. The impacts associated with packaging disposal are included with the installation phase as per PCR requirements.

2.12 USE CONDITIONS

No special conditions of use are noted.

2.13 REFERENCE SERVICE LIFE

The Reference Service Life (RSL) of the flooring product is one year based on PCR requirements.

2.14 RE-USE PHASE

The flooring product is not reused at end-of-life.

2.15 DISPOSAL

At end-of-life, the products may be disposed of in a landfill or via incineration. Although in some instances, vinyl flooring can be recycled into other products, the practice is not typical, nor widely available as a disposal route for the products in the consumer markets considered. It is assumed that no components of the product are recycled at end-of-life.

2.16 FURTHER INFORMATION

Further information on the product can be found on the manufacturer's website www.oneflor-europe.com.

3. LCA: Calculation Rules

3.1 FUNCTIONAL UNIT

The functional unit used in the study is defined as 1 m² of floor covering installed for use over a 1-year period. The corresponding reference flow for each product system is presented in Table 5. For the present assessment, a reference service lifetime (RSL) is 1-year in conformance with the PCR.

Table 5. *Reference flow and RSL for the flooring product.*

Product	Reference Flow (kg/m ²)	Reference Service Lifetime (yr)
MERCURY RIGID SPC Click	8.77	1

3.2 SYSTEM BOUNDARY

The scope of the EPD is cradle-to-grave and Module D, including raw material extraction and processing, transportation, product manufacture, product delivery, installation and use, and product disposal. The following processes are excluded from the system boundary, consistent with the PCR:

- Construction activities, capital equipment, and infrastructure
- Maintenance and operation of capital equipment
- Personnel travel and resource use

The life cycle phases included in the EPD scope are described in Table 6 and illustrated in Figure 1.

Table 6. *The modules and unit processes included in the scope for the flooring product system.*

Module	Module description from the PCR	Unit Processes Included in Scope
A1	Extraction and processing of raw materials; any reuse of products or materials from previous product systems; processing of secondary materials; generation of electricity from primary energy resources; energy, or other, recovery processes from secondary fuels	Extraction and processing of raw materials for the flooring components.
A2	Transport (to the manufacturer)	Transport of component materials to the manufacturing facility
A3	Manufacturing, including ancillary material production	Manufacturing of the flooring product and packaging (incl. upstream unit processes)
A4	Transport (to the building site)	Transport of product (including packaging) to the building site
A5	Construction-installation process	Impacts from the installation of the product are assumed negligible. Impacts from the production, transport and disposal of waste material associated with installation are included in this phase in addition to impacts from packaging disposal.
B1	Product use	Module not applicable
B2	Product maintenance	Maintenance of products over the product RSL, including periodic cleaning.
B3	Product repair	Module not applicable
B4	Product replacement	Module not applicable
B5	Product refurbishment	Module not applicable
B6	Operational energy use by technical building systems	Module not applicable
B7	Operational water use by technical building systems	Module not applicable
C1	Deconstruction, demolition	Demolition of the product is accomplished using hand tools with no associated emissions and negligible impacts
C2	Transport (to waste processing)	Transport of flooring product to waste treatment at end-of-life
C3	Waste processing for reuse, recovery and/or recycling	The product is disposed of by landfilling which requires no waste processing
C4	Disposal	Disposal of flooring product in municipal landfill
D	Reuse-recovery-recycling potential	Module Not Declared

It is noted that generation of electricity used in the manufacturing process should be included in stage A1 as specified by EN 15804. However, since the separation of combustion emissions and energy resource extraction for electricity generation could not be accomplished with the LCI data used for the modeling, impacts from electricity use are modeled in the manufacturing stage A3 and impacts from stages A1 through A3 are combined and reported in aggregate in the LCA results presented in this EPD.




Figure 1. Flow diagram for the life cycle of the flooring product.

3.3 PRODUCT SPECIFIC CALCULATION FOR USE PHASE

The recommended cleaning regime is highly dependent on the use of the premises where the floor covering is installed. In high traffic areas more frequent cleaning will be needed compared to areas where there is low traffic. For the purposes of this EPD, average maintenance (moderate traffic levels) is presented based on typical installations.

3.4 UNITS

All data and results are presented using SI units.

3.5 ESTIMATES AND ASSUMPTIONS

- Electricity use at the manufacturing facility was allocated to the product based on the product area as a fraction of the total production.
- The production facility under review is located in China. Ecoinvent inventory datasets for the country-specific energy grid were used to model resource use and emissions from electricity use at the manufacturing facility.
- The Reference Service Life (RSL) of the products was modeled based on PCR guidance.
- Downstream transport was modeled based on information provided by the manufacturer representing distribution to consumer markets in Europe.
- The maintenance phase of the product life cycle was modeled based on information provided by the manufacturer including recommended installation and cleaning methods, as well as cleaning frequency.
- For the product end-of-life, disposal of product and product packaging is modeled based on the PCR guidance regarding recycling rates of product and packaging materials.
- For final disposal of the packaging material and flooring product at end-of-life, all materials are assumed to be transported 161 km by diesel truck to either landfill or material reclamation facility (for recycling). Datasets representing disposal in a landfill and waste incineration are from Ecoinvent.
- Inventory data for some material components was unavailable and modeled using proxy datasets from the Ecoinvent LCI databases.

The PCR requires the results for several inventory flows related to construction products to be reported including energy and resource use and waste and outflows. These are aggregated inventory flows, and do not characterize any potential impact; results should be interpreted considering this limitation.

3.6 CUT-OFF RULES

According to the PCR, processes contributing greater than 5% of the total environmental impact indicator for each impact are included in the inventory. No data gaps were allowed which were expected to significantly affect the outcome of the indicator results. No known flows are deliberately excluded from this EPD.

3.7 DATA SOURCES

Primary data were provided for the manufacturing facility. The sources of secondary LCI data are the Ecoinvent database.

Table 7. Data sources for the flooring product.

Component	Dataset ¹	Data Source	Publication Date
PRODUCT			
PVC			
Polyvinyl Chloride	market for polyvinylchloride, bulk polymerised polyvinylchloride, bulk polymerised Cutoff, S/GLO	EI v3.10	2023
Filler			
Calcium Carbonate	limestone production, crushed, washed limestone, crushed, washed Cutoff, S/RoW	EI v3.10	2023
Plasticizer			
PVC Plasticizer	diethyl terephthalate production diethyl terephthalate Cutoff, S/GLO	EI v3.10	2023
Stabilizer			
Stabilizer	market for chemical, organic chemical, organic Cutoff, S/GLO	EI v3.10	2023
	market for chemicals, inorganic chemical, inorganic Cutoff, S/GLO	EI v3.10	2023
	solvent production, organic solvent, organic Cutoff, S/GLO	EI v3.10	2023
	limestone production, crushed, washed limestone, crushed, washed Cutoff, S/RoW	EI v3.10	2023
	market for zinc oxide zinc oxide Cutoff, S/GLO	EI v3.10	2023
Pigments			
Carbon Black	carbon black production carbon black Cutoff, S/GLO	EI v3.10	2023
TiO ₂	market for titanium dioxide titanium dioxide Cutoff, S/RoW	EI v3.10	2023
Others			
ESBO	market for soybean oil, refined soybean oil, refined Cutoff, S/GLO	EI v3.10	2023
Adhesive	polyurethane adhesive production polyurethane adhesive Cutoff, S/GLO	EI v3.10	2023
Acrylic resin	methyl acrylate production methyl acrylate Cutoff, S/GLO	EI v3.10	2023
Coating	market for chemical, organic chemical, organic Cutoff, S/GLO	EI v3.10	2023
PACKAGING			
Cardboard/Paper	corrugated board box production corrugated board box Cutoff, S/RoW; containerboard production, linerboard, testliner containerboard, linerboard Cutoff, S/RoW; kraft paper production kraft paper Cutoff, S/RoW	EI v3.10	2023
Plastics	packaging film production, low density polyethylene packaging film, low density polyethylene Cutoff, S/RoW; polyethylene production, low density, granulate polyethylene, low density, granulate Cutoff, S/RoW	EI v3.10	2023
Adhesive	polyurethane adhesive production polyurethane adhesive Cutoff, S/GLO	EI v3.10	2023
Wood	EUR-flat pallet production EUR-flat pallet Cutoff, S/RoW	EI v3.10	2023
TRANSPORT			
Road transport	market for transport, freight, lorry 16-32 metric ton, EURO4 transport, freight, lorry 16-32 metric ton, EURO4 Cutoff, S/RoW	EI v3.10	2023
Ship transport	transport, freight, sea, container ship transport, freight, sea, container ship Cutoff, S/GLO	EI v3.10	2023
MAINTENANCE			
Neutral cleaner	ethoxylated alcohol (AE7) production, petrochemical ethoxylated alcohol (AE7) Cutoff, U - RER fatty acid production, from palm oil fatty acid Cutoff, U - RER tap water production, conventional treatment tap water Cutoff, U - Europe without Switzerland	EI v3.10	2023
Electricity	market for electricity, low voltage electricity, low voltage Cutoff, S/RER	EI v3.10	2023
Water	water production, conventional treatment tap water Cutoff, U - Europe without Switzerland	EI v3.10	2023
WASTE DISPOSAL			
Landfill ²	treatment of municipal solid waste, sanitary landfill municipal solid waste Cutoff, S/RoW	EI v3.10	2023
	treatment of waste polyvinylchloride, sanitary landfill waste polyvinylchloride Cutoff, S/RoW	EI v3.10	2023
RESOURCES			
Grid electricity	market group for electricity, medium voltage electricity, medium voltage Cutoff, S/CN	EI v3.10	2023
Heat – light fuel oil	heat production, light fuel oil, at industrial furnace 1MW heat, district or industrial, other than natural gas Cutoff, S/RoW	EI v3.10	2023
Heat – steam	market for heat, from steam, in chemical industry heat, from steam, in chemical industry Cutoff, S/RoW	EI v3.10	2023
Water	tap water production, conventional treatment tap water Cutoff, S/RoW	EI v3.10	2023

¹ The impact of different materials used as proxies is estimated to be less than +/-10%² RoW LCI datasets are used as a proxy for C4 {RER} LCI datasets, as {RER} LCI datasets were not available.

3.8 DATA QUALITY

The data quality assessment addressed the following parameters: time-related coverage, geographical coverage, technological coverage, precision, completeness, representativeness, consistency, reproducibility, sources of data, and uncertainty.

Table 8. *Data quality assessment for the flooring product system.*

Data Quality Parameter	Data Quality Discussion
Time-Related Coverage: Age of data and the minimum length of time over which data is collected	The most recent available data are used, based on other considerations such as data quality and similarity to the actual operations. Typically, these data are less than 5 years old. All of the data used represented an average of at least one year's worth of data collection, and up to three years in some cases. Manufacturer-supplied data (primary data) are based on annual production for 2023.
Geographical Coverage: Geographical area from which data for unit processes is collected to satisfy the goal of the study	The data used in the analysis provide the best possible representation available with current data. Electricity use for product manufacture is modeled using representative data for China. Surrogate data used in the assessment are representative of global or European operations. Data representative of European operations is considered sufficiently similar to actual processes. Data representing product disposal are based on regional statistics.
Technology Coverage: Specific technology or technology mix	For the most part, data are representative of the actual technologies used for processing, transportation, and manufacturing operations. Representative fabrication datasets, specific to the type of material, are used to represent the actual processes, as appropriate.
Precision: Measure of the variability of the data values for each data expressed	Precision of results are not quantified due to a lack of data. Data collected for operations were typically averaged for one or more years and over multiple operations, which is expected to reduce the variability of results.
Completeness: Percentage of flow that is measured or estimated	The LCA model included all known mass and energy flows for production of the flooring product. In some instances, surrogate data used to represent upstream and downstream operations may be missing some data which is propagated in the model. No known processes or activities contributing to more than 1% of the total environmental impact for each indicator are excluded.
Representativeness: Qualitative assessment of the degree to which the data set reflects the true population of interest	Data used in the assessment represent typical or average processes as currently reported from multiple data sources and are therefore generally representative of the range of actual processes and technologies for production of these materials. Considerable deviation may exist among actual processes on a site-specific basis; however, such a determination would require detailed data collection throughout the supply chain back to resource extraction.
Consistency: Qualitative assessment of whether the study methodology is applied uniformly to the various components of the analysis	The consistency of the assessment is considered to be high. Data sources of similar quality and age are used; with a bias towards Ecoinvent v3.10 data where available. Different portions of the product life cycle are equally considered.
Reproducibility: Qualitative assessment of the extent to which information about the methodology and data values would allow an independent practitioner to reproduce the results reported in the study	Based on the description of data and assumptions used, this assessment would be reproducible by other practitioners. All assumptions, models, and data sources are documented.
Sources of the Data: Description of all primary and secondary data sources	Data representing energy use at the manufacturing facility represents an annual average and are considered of high quality due to the length of time over which these data are collected, as compared to a snapshot that may not accurately reflect fluctuations in production. For secondary LCI data, Ecoinvent v3.10 LCI data are used.
Uncertainty of the Information: Uncertainty related to data, models, and assumptions	Uncertainty related to materials in the product and packaging is low. Actual supplier data for upstream operations were not available and the study relied upon the use of existing representative datasets. These datasets contained relatively recent data (<10 years) but lacked geographical representativeness. Uncertainty related to the impact assessment methods used in the study are high. The impact assessment method required by the PCR includes impact potentials, which lack characterization of providing and receiving environments or tipping points.

3.9 PERIOD UNDER REVIEW

The LCA results are based on annual production data for calendar year 2023.

3.10 ALLOCATION

Resource use at the manufacturing facility (e.g., water and energy) was allocated to the products based on the product area as a fraction of the total facility production volume (i.e., area-based allocation). Area-based allocation was deemed most appropriate for the flooring products as total facility production was available as total square meters of product. Electricity use at the manufacturing facility was modeled using ecoinvent inventory datasets for the country-specific electrical grid.

Impacts from transportation, including product distribution to point of sale, were attributed to the products based on the mass of material and distance transported.

3.11 COMPARABILITY

The PCR this EPD is based on was not written to support comparative assertions. EPDs based on different PCRs, or different calculation models, may not be comparable. When attempting to compare EPDs or life cycle impacts of products from different companies, the user should be aware of the uncertainty in the final results, due to and not limited to, the practitioner's assumptions, the source of the data used in the study, and the specifics of the product modeled.

4. LCA: Scenarios and Additional Technical Information

Delivery and Installation stage (A4 - A5)

Distribution of the flooring product to the point of sale is included, based on data from the manufacturer. Average transport distances for distribution of the product from the manufacturing facilities to distribution centers in Europe were provided by the manufacturer. Transport by diesel truck from the distribution centers to the point of installation is also included, based on information provided by the manufacturer. Transportation parameters for modeling product distribution are summarized in Table 9.

Table 9. Product distribution parameters by transport mode.

Parameter	Unit	Value	
Ground transport			
Fuel type	-	Diesel	
Liters of fuel	L/100km	18.7	
Vehicle type	-	Diesel truck	
Capacity utilization	%	76	
Ocean transport			
Fuel type	-	Fuel oil	
Grams of fuel	g/tkm	2.52	
Vehicle type	-	Ocean freighter	
Capacity utilization	%	70	
Product Name	Gross mass transported (kg)	Transport Distance (km)	
		Road	Ship
MERCURY RIGID SPC Click	9.29	750	19,000

Installation of the product and periodic cleaning are included in the life cycle Use phase. The manufacturer provided installation and maintenance guidelines detailing the recommended installation methods, as well as maintenance and cleaning guidance. For the current assessment, the impacts associated with the product installation are assumed negligible. Approximately 4% of the product mass is assumed lost as waste during product installation which is landfilled. The VOC emissions associated with the installation, use and maintenance of the products are negligible.

Impacts associated with the disposal of packaging materials are also included in the installation life cycle phase. Assumed recycling rates for packaging component materials are based on the PCR requirements and are summarized in Table 10.

Table 10. *Recycling rates for packaging materials at end-of-life.*

Material	Packaging Recycling Rate (%)
Recycling Rates	
Plastics	40.3%
Paper & Pulp	82.8%
Wood	39.8%
Disposal of Non-recyclables	
Landfill	55%
Incineration	45%

Table 11 summarizes the relevant parameters for the product installation phase including biogenic carbon emissions and removals, and wastes associated with product packaging.

Table 11. *Installation parameters for the flooring product, per 1 m².*

Parameter		Value
Ancillary materials – adhesive (kg)		0.00
Net freshwater consumption (m ³)		0.00
Electricity consumption (kWh)		0.00
Product loss per functional unit (kg)		0.395
Waste materials generated by product installation (kg)		0.944
Output materials resulting from on-site waste processing (kg)		n/a
Mass of packaging waste (kg)	Plastic	4.91x10 ⁻³
	Corrugate	0.283
	Wood	0.260
	Adhesive	0.002
Biogenic carbon contained in packaging (kg CO ₂) ¹		0.952
Direct emissions (kg)		3.00

¹ Biogenic carbon contained in packaging is calculated assuming the carbon content of corrugate and wood is 50% by weight.

Maintenance stage (B2)

According to the manufacturer, typical maintenance involves regular sweeping and damp mopping, as well as periodic machine cleaning of the vinyl flooring. The present assessment is based on a recommended weekly cleaning schedule including sweeping and mopping with a neutral cleaner and monthly machine cleaning. The parameters used to model the product maintenance are summarized in Table 12.

Table 12. Maintenance parameters for the flooring product, per 1 m².

Parameter	Unit	Value
Maintenance cycle	Cycles / RSL	52
Maintenance cycle	Cycles / ESL	52
Maintenance process	-	Damp mopping
Net freshwater consumption	m ³ /m ² /yr	0.0058
Cleaning agent	kg/m ² /yr	0.119
Maintenance process	-	Machine cleaning
Electricity	kWh/m ² /yr	0.022
Further assumptions	-	Moderate traffic; weekly maintenance

Disposal stage (C1 - C4)

The disposal stage includes removal of the products (C1); transport of the flooring products to waste treatment facilities (C2); waste processing (C3); and associated emissions as the product degrades in a landfill or is burned in an incinerator (C4). For the flooring products, no emissions are generated during demolition (C1) while no waste processing (C3) is required for incineration or landfill disposal.

At end-of-life, the product is assumed to be disposed of in a landfill per PCR requirements. Transportation for end-of-life scenarios was modeled assuming a distance of 161 km from the point of product use to a landfill, material recovery center, or waste incinerator. Ecoinvent datasets are used to model the impacts associated with incineration and landfilling, which does not include energy recovery from landfill gas. The end-of-life disposal parameters are summarized in Table 13.

Table 13. End-of-life disposal scenario parameters for the flooring product.

Parameter	Value
Assumptions for scenario development	100% landfill
Collection process	
Collected with mixed construction waste (kg)	8.77
Recovery	n/a
Landfill disposal (kg)	8.77
Removals of biogenic carbon (kg CO ₂ eq) ¹	n/a

5. LCA: Results

Results of the Life Cycle Assessment are presented below. It is noted that LCA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks. All LCA results are stated to three significant figures in agreement with the PCR for this flooring product and therefore the sum of the total values may not exactly equal 100%.

The impact indicators specified by the PCR include:

- Potential for Global Warming,
- Acidification Potential,
- Eutrophication Potential,
- Ozone Depletion Potential,
- Photochemical Ozone (smog) Creation Potential.
- Ecotoxicity,
- Human Toxicity, and
- Land Use/Land Occupation

Impact category indicators for acidification, eutrophication, ozone depletion potential and photochemical ozone creation are estimated using the characterization factors¹, as prescribed by the PCR, including from CML-IA and ReCiPe methodologies as well as those defined by EN 15804 reference package based on EF 3.0. Impact indicators for Ecotoxicity and Human Toxicity are estimated using the USEtox 2.02 characterization method, while Land Occupation impacts are estimated using the ReCiPe 2016 version 1.1 methodology. The impact category indicators included in the assessment are summarized below.

These impact categories are globally deemed mature enough to be included in Type III environmental declarations. Other categories are being developed and defined and LCA should continue making advances in their development. However, the EPD users shall not use additional measures for comparative purposes.

Note that the use of the results of modules A1-A3 without considering the results of module C is discouraged.

¹ <https://www.environdec.com/resources/indicators>

Table 14. Core Life Cycle Impact Assessment results per 1 m² of the flooring products over a 1-yr time horizon. Results reported in MJ are calculated using lower heating values. All values are rounded to three significant digits. **(MERCURY RIGID SPC Click)**

Impact Category	Units	A1-A3	A4	A5	B2	C2	C4
Core Indicators							
Global Warming Potential - total (GWP-total)	kg CO2 eq	11.2	3.20	1.27	4.56x10 ⁻²	0.272	3.38
	%	58%	16%	6.6%	0.24%	1.4%	17%
Global Warming Potential - fossil fuels (GWP-fossil)	kg CO2 eq	12.9	3.20	0.886	5.55x10 ⁻²	0.271	0.533
	%	72%	18%	5%	0.31%	1.5%	3%
Global Warming Potential - biogenic (GWP-biogenic)	kg CO2 eq	-1.66	3.37x10 ⁻⁴	0.384	-3.53x10 ⁻²	1.87x10 ⁻⁴	2.84
	%	-110%	0.022%	25%	-2.3%	0.012%	180%
Global Warming Potential - land use and land use change (GWP-luluc)	kg CO2 eq	1.03x10 ⁻²	1.41x10 ⁻³	5.52x10 ⁻⁴	2.55x10 ⁻²	8.93x10 ⁻⁵	8.83x10 ⁻⁵
	%	27%	3.7%	1.5%	67%	0.24%	0.23%
Global warming potential (GWP-GHG)	kg CO2 eq	12.1	3.20	1.11	8.11x10 ⁻²	0.272	2.78
	%	62%	16%	5.7%	0.41%	1.4%	14%
Depletion potential of the stratospheric ozone layer (ODP)	kg CFC-11 eq.	3.45x10 ⁻⁶	5.34x10 ⁻⁸	1.60x10 ⁻⁷	1.38x10 ⁻⁹	5.43x10 ⁻⁹	2.76x10 ⁻⁹
	%	94%	1.5%	4.4%	0.038%	0.15%	0.075%
Acidification potential, Accumulated Exceedance (AP)	mol H+ eq.	5.74x10 ⁻²	5.99x10 ⁻²	6.08x10 ⁻³	3.59x10 ⁻⁴	1.08x10 ⁻³	1.08x10 ⁻³
	%	46%	48%	4.8%	0.29%	0.86%	0.86%
Eutrophication potential - freshwater (EP-freshwater)	kg P eq.	3.20x10 ⁻³	1.49x10 ⁻⁴	1.85x10 ⁻⁴	2.55x10 ⁻⁵	1.82x10 ⁻⁵	3.18x10 ⁻⁴
	%	82%	3.8%	4.8%	0.65%	0.47%	8.2%
Eutrophication potential - marine (EP-marine)	kg N eq.	1.02x10 ⁻²	1.56x10 ⁻²	2.11x10 ⁻³	2.16x10 ⁻⁴	4.07x10 ⁻⁴	7.81x10 ⁻³
	%	28%	43%	5.8%	0.59%	1.1%	21%
Eutrophication potential - terrestrial (EP-terrestrial)	mol N eq.	0.127	0.173	1.71x10 ⁻²	9.29x10 ⁻⁴	4.44x10 ⁻³	3.72x10 ⁻³
	%	39%	53%	5.3%	0.28%	1.4%	1.1%
Photochemical Ozone Creation Potential (POCP)	kg NMVOC eq.	5.07x10 ⁻²	4.90x10 ⁻²	5.98x10 ⁻³	3.15x10 ⁻⁴	1.64x10 ⁻³	2.00x10 ⁻³
	%	46%	45%	5.5%	0.29%	1.5%	1.8%
Depletion of abiotic resources - minerals and metals (kg Sb eq) ¹	kg Sb eq	1.05x10 ⁻⁴	6.23x10 ⁻⁶	5.16x10 ⁻⁶	7.29x10 ⁻⁷	8.95x10 ⁻⁷	2.74x10 ⁻⁷
	%	89%	5.3%	4.4%	0.61%	0.75%	0.23%
Depletion of abiotic resources - fossil fuels (MJ) ¹	MJ	220	41.7	13.7	1.25	3.84	2.50
	%	78%	15%	4.8%	0.44%	1.4%	0.88%
Water use (m3 depriv.) ¹	m3 depriv	3.05	0.154	0.153	5.48x10 ⁻²	1.85x10 ⁻²	1.98x10 ⁻²
	%	88%	4.5%	4.4%	1.6%	0.54%	0.57%

1) The results of this environmental impact indicator shall be used with care as uncertainties on these results are high or as there is limited experience with the indicator.

Table 15. Additional Life Cycle Impact Assessment results per 1 m² of the flooring products over a 1-yr time horizon. Results reported in MJ are calculated using lower heating values. All values are rounded to three significant digits. **(MERCURY RIGID SPC Click)**

Impact Category	Units	A1-A3	A4	A5	B2	C2	C4
Additional Indicators							
Potential incidence of disease due to PM emissions (PM)	Disease Incidence	6.84x10 ⁻⁷	1.63x10 ⁻⁷	5.65x10 ⁻⁸	4.35x10 ⁻⁹	2.20x10 ⁻⁸	1.79x10 ⁻⁸
	%	72%	17%	6%	0.46%	2.3%	1.9%
Potential Human exposure efficiency relative to U235 (IRP)2	kBq U235 eq.	0.676	3.46x10 ⁻²	3.31x10 ⁻²	1.35x10 ⁻²	4.92x10 ⁻³	4.45x10 ⁻³
	%	88%	4.5%	4.3%	1.8%	0.64%	0.58%
Potential Comparative Toxic Unit for ecosystems (ETP-fw)	CTUe	101	8.97	10.3	0.704	1.03	435
	%	18%	1.6%	1.8%	0.13%	0.18%	78%
Potential Comparative Toxic Unit for humans - cancer effects (HTP-c)1	CTUh	4.85x10 ⁻⁸	1.72x10 ⁻⁸	3.30x10 ⁻⁹	1.97x10 ⁻¹⁰	1.91x10 ⁻⁹	7.32x10 ⁻¹⁰
	%	67%	24%	4.6%	0.27%	2.7%	1%
Potential Comparative Toxic Unit for humans - non-cancer effects (HTP-nc)1	CTUh	3.07x10 ⁻⁷	1.80x10 ⁻⁸	1.73x10 ⁻⁸	7.84x10 ⁻¹⁰	2.47x10 ⁻⁹	2.17x10 ⁻⁸
	%	84%	4.9%	4.7%	0.21%	0.67%	5.9%
Potential Soil quality index (SQP)1	Dimensionless	116	13.0	6.41	1.35	2.28	5.16
	%	80%	9%	4.4%	0.93%	1.6%	3.6%

1) The results of this environmental impact indicator shall be used with care as uncertainties on these results are high or as there is limited experience with the indicator.

2) This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Table 16. Resource use per 1 m² of the flooring products over a 1-yr time horizon. Results reported in MJ are calculated using lower heating values. All values are rounded to three significant digits. **(MERCURY RIGID SPC Click)**

Parameter	Units	A1-A3	A4	A5	B2	C2	C4
Resources							
Use of renewable primary energy resources used as energy carrier (PERE)	MJ	13.8	0.490	0.657	1.01	6.51x10 ⁻²	5.85x10 ⁻²
	%	86%	3%	4.1%	6.3%	0.41%	0.36%
Use of renewable primary energy resources used as raw materials (PERM)	MJ	9.32	0.00	0.420	0.00	0.00	0.00
	%	96%	0%	4.3%	0%	0%	0%
Total use of renewable primary energy resources (PERT)	MJ	23.1	0.490	1.08	1.01	6.51x10 ⁻²	5.85x10 ⁻²
	%	90%	1.9%	4.2%	3.9%	0.25%	0.23%
Use of non renewable primary energy resources used as energy carrier (PENRE)	MJ	175	41.4	13.6	1.25	3.81	2.48
	%	74%	17%	5.7%	0.53%	1.6%	1%
Use of non renewable primary energy resources used as raw materials (PENRM)	MJ	42.7	0.00	2.50x10 ⁻³	0.00	0.00	0.00
	%	100%	0%	0.0059%	0%	0%	0%
Total use of non renewable primary energy resources (PENRT)	MJ	220	41.7	13.7	1.28	3.84	2.50
	%	78%	15%	4.8%	0.45%	1.4%	0.88%
Use of secondary materials (SM)	kg	0.445	3.63x10 ⁻²	2.23x10 ⁻²	8.12x10 ⁻³	4.33x10 ⁻³	0.00
	%	86%	7%	4.3%	1.6%	0.84%	0%
Use of renewable secondary fuels (RSF)	MJ	0.00	0.00	0.00	0.00	0.00	0.00
	%	0%	0%	0%	0%	0%	0%
Use of non renewable secondary fuels (NRSF)	MJ	0.00	0.00	0.00	0.00	0.00	0.00
	%	0%	0%	0%	0%	0%	0%
Use of net fresh water (FW)	m3	8.01x10 ⁻²	4.03x10 ⁻³	2.04x10 ⁻³	7.30x10 ⁻³	5.09x10 ⁻⁴	-3.27x10 ⁻²
	%	130%	6.6%	3.3%	12%	0.83%	-53%

Table 17. Waste and outflows per 1 m² of the flooring products over a 1-yr time horizon. Results reported in MJ are calculated using lower heating values. All values are rounded to three significant digits. **(MERCURY RIGID SPC Click)**

Parameter	Units	A1-A3	A4	A5	B2	C2	C4
Wastes							
Hazardous waste disposed (HWD)	Kg	3.38x10 ⁻³	2.44x10 ⁻⁴	1.77x10 ⁻⁴	1.38x10 ⁻⁵	2.58x10 ⁻⁵	1.65x10 ⁻⁵
	%	88%	6.3%	4.6%	0.36%	0.67%	0.43%
Non hazardous waste disposed (NHWD)	Kg	0.00	0.00	0.00	0.00	0.00	0.00
	%	0%	0%	0%	0%	0%	0%
Radioactive waste disposed (RWD)	Kg	1.69x10 ⁻⁴	8.55x10 ⁻⁶	8.25x10 ⁻⁶	3.46x10 ⁻⁶	1.22x10 ⁻⁶	1.08x10 ⁻⁶
	%	88%	4.5%	4.3%	1.8%	0.64%	0.57%
Components for re-use (CRU)	Kg	0.00	0.00	0.00	0.00	0.00	0.00
	%	0%	0%	0%	0%	0%	0%
Materials for recycling (MFR)	Kg	0.00	0.00	0.340	0.00	0.00	0.00
	%	0%	0%	100%	0%	0%	0%
Materials for energy recovery (MER)	Kg	0.00	0.00	0.00	0.00	0.00	0.00
	%	0%	0%	0%	0%	0%	0%
Exported electrical energy (EEE)	MJ	6.54x10 ⁻²	4.22x10 ⁻³	3.21x10 ⁻³	2.15x10 ⁻³	6.45x10 ⁻⁴	0.00
	%	86%	5.6%	4.2%	2.8%	0.85%	0%
Exported thermal energy (EET)	MJ	0.00	0.00	0.00	0.00	0.00	0.00
	%	0%	0%	0%	0%	0%	0%

6. LCA: Interpretation

With few exceptions, impacts over a single product life cycle are dominated by the raw material extraction and processing (A1), the product manufacturing (A3) and the product distribution (A4) stages. Impacts related phase A1 are associated primarily with the extraction and processing of plastics and plasticizers, while manufacturing impacts are dominated by electricity consumption at the production facility.

7. References

- Life Cycle Assessment of Life Cycle Assessment of Luxury Vinyl Flooring. March 2025. Report. Prepared for client.
- Product Category Rule.PCR2019:14. Construction Products. International EPD® System. Version 1.3.4. VALID UNTIL: 2025-06-20.
- Complementary Product Category Rules (c-PCR) To PCR 2019:14. Resilient, Textile And Laminate Floor Coverings (EN 16810:2017). International EPD® System. Version 2024-04-30, VALID UNTIL: 2025-06-20
- EN 15804:2012+A2:2019/AC:2021. Sustainability of construction works. Environmental product declarations. Core rules for the product category of construction products.
- ISO 14025:2006 Environmental labels and declarations – Type III environmental declarations – Principles and ISO procedures
- ISO 14040: 2006/ AMD 1:2020 Environmental Management – Life cycle assessment – Principles and framework
- ISO 14044: 2006/AMD 1:2017/ AMD 2:2020 Environmental Management – Life cycle assessment – Requirements and Guidelines.
- CML 4.1 baseline, from Institute of Environmental Sciences Faculty of Science University of Leiden, Netherlands.
- Rosenbaum (2008). Rosenbaum, R.K., Bachmann, T.M., Gold, L.S. et al. USEtox - the UNEP-SETAC toxicity model: recommended characterisation factors for human toxicity and freshwater ecotoxicity in life cycle impact assessment. Int J Life Cycle Assess (2008) 13: 532. doi:10.1007/s11367-008-0038-4. USEtox version 2.02.
- ReCiPe Mid/Endpoint method, version 1.13 November 2016.
<https://sites.google.com/site/lciarecipe/characterisation-and-normalisation-factors>
- Ecoinvent Centre (2023) Ecoinvent data from v3.10 Swiss Center for Life Cycle Inventories, Dubendorf, 2022, <http://www.ecoinvent.org>
- SCS Type III Environmental Declaration Program: Program Operator Manual. V12.0 December 2023. SCS Global Services

For more information, contact:



Oneflor Europe bv

Wittestraat 10 - B-8501 HEULE

Belgium

www.oneflor-europe.com | info@oneflor-europe.com

+32 (0)56 41 06 04



SCS Global Services

2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

Main +1.510.452.8000 | fax +1.510.452.8001